

FAG 31320-X参数

说明		T7GB100		根据 DIN ISO 355 的 对应型号	
尺寸	d	100	mm	-	
	D	215	mm	-	
	T	56.5	mm	-	
	a	68	mm	-	
	B	51	mm	-	
	C	35	mm	-	
	$C_a \text{ min}$	7	mm	-	
	$C_b \text{ min}$	21.5	mm	-	
	$D_a \text{ max}$	201	mm	-	
	$D_a \text{ min}$	168	mm	-	
	$D_b \text{ min}$	202	mm	-	
	d_1	159.5	mm	-	
	$d_a \text{ max}$	121	mm	-	
	$d_b \text{ min}$	114	mm	-	
	$r_{1, 2} \text{ min}$	4	mm	-	
	$r_{3, 4} \text{ min}$	3	mm	-	
	$r_a \text{ max}$	4	mm	-	
	$r_b \text{ max}$	3	mm	-	
	重量	m	8810	g	质量
	基本额定载荷	C_r	385000	N	基本额定动载荷，径向
C_{0r}		480000	N	基本额定静载荷，径向	
计算系数	e	0.83		-	
	Y	0.73		-	
	Y_0	0.4		-	
疲劳极限载荷	C_{ur}	51000	N	疲劳极限载荷，径向	
极限转速	n_G	3200	r/min	极限转速	

FAG 31320-X图片

