

## NSK N211参数

|        |      |       |       |      |
|--------|------|-------|-------|------|
| 型号     | 型号   | N211  |       | -    |
| 外形尺寸   | SD   | 55    | mm    | 内径   |
|        | D    | 100   | mm    | 外径   |
|        | B    | 21    | mm    | 宽度   |
|        | R    | 1.5   | mm    | (最小) |
|        | R1   | 1.1   | mm    | (最小) |
|        | FW   | 0.0   | mm    | -    |
|        | EW   | 88.5  | mm    | -    |
| 基本额定载荷 | CR1  | 58000 | N     | 动载荷  |
|        | COR1 | 62500 | N     | 静载荷  |
|        | CR2  | 5900  | kgf   | 动载荷  |
|        | COR2 | 6350  | kgf   | 静载荷  |
| 极限转速   | LG   | 6300  | 1/min | 脂润滑  |
|        | LO   | 7500  | 1/min | 油润滑  |
| 安装尺寸   | DA1  | 63.0  | mm    | (最小) |
|        | DBB1 | 0.0   | mm    | (最小) |
|        | DBB2 |       | mm    | (最大) |
|        | DC   |       | mm    | (最小) |
|        | DD1  |       | mm    | (最小) |
|        | DA2  | 0.0   | mm    | (最大) |
|        | DB1  | 93.5  | mm    | (最小) |
|        | DB2  | 91.0  | mm    | (最小) |
|        | RA   | 1.5   | mm    | (最大) |
|        | RB   | 1.0   | mm    | (最大) |
| 重量     | MASS | 634   | g     | 重量   |

## NSK N211图片

参考资料:<http://www.sozhou.com/p/0583eac4.html>

