





SKF 71910 CD/HCP4A参数

主要尺寸	d	50	mm	—
	D	72	mm	—
	B	12	mm	—
基本额定载荷	C	13500	N	动载荷
	C_0	10400	N	静载荷
疲劳载荷极限	P_u	440	N	—
可达转速	Grease	22000	r/min	—
	Oil-air	34000	r/min	—
重量	重量	120	g	—
型号	型号	71910 CD/HCP4A	—	—

SKF 71910 CD/HCP4A图片



Ball diameter 6,35

Number of balls 25

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
50	100	200	400

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
47	63	87	122

Reference grease quantity [cm³]

G_{ref} 1,7

计算系数

for equivalent bearing load

f_0 10,7

for preload in mounted bearing sets

f 1,13

f_1 1





f_{2A} 1

f_{2B} 1,07

f_{2C} 1,12

f_{2D} 1,18

f_{HC} 1,04



Ball diameter 6,35
Number of balls 25

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
50	100	200	400

Static axial stiffness [N/ μ m]

(guideline value)

预载荷等级

A	B	C	D
47	63	87	122

Reference grease quantity [cm³]

G_{ref} 1,7

计算系数

for equivalent bearing load

f_0 10,7

for preload in mounted bearing sets

f 1,13

f_1 1

f_{2A} 1

f_{2B} 1,07

f_{2C} 1,12

f_{2D} 1,18

f_{HC} 1,04