

## NACHI 359S/354A参数

|        |             |        |       |      |
|--------|-------------|--------|-------|------|
| 外形尺寸   | d           | 46.038 | mm    | 内径   |
|        | D           | 85.001 | mm    | 外径   |
|        | T           | 20.638 | mm    | 宽度   |
|        | B           | 21.692 | mm    | 宽度   |
|        | C           | 17.463 | mm    | 宽度   |
|        | r1(min)     | 2.4~   | mm    | 径向   |
|        | r1(min)     | 2.4~   | mm    | 径向   |
|        | r2(min)     | 1.3~   | mm    | 径向   |
|        | r2(min)     | 1.3~   | mm    | 径向   |
| 载荷中心   | a           | 5.1    | mm    | 载荷中心 |
| 安装尺寸   | da(min)     | 55     | mm    | (最小) |
|        | db(max)     | 51     | mm    | (最大) |
|        | Da(min)     | 77     | mm    | (最小) |
|        | Db(min)     | 80     | mm    | (最小) |
|        | r1a(max)    | 2.4    | mm    | (最大) |
|        | r2a(max)    | 1.3    | mm    | (最大) |
| 重量     | Mass (Cone) | 323    | g     | 内圈   |
|        | Mass (Cup)  | 160    | g     | 外圈   |
| 基本额定载荷 | Cr          | 71800  | N     | 动载荷  |
|        | Cor         | 81700  | N     | 静载荷  |
| 极限速度   | Grease      | 4600   | r/min | 脂润滑  |
|        | Oil         | 6200   | r/min | 油润滑  |

## NACHI 359S/354A图片

参考资料:<http://www.sozhou.com/p/0fb83dbe.html>

