

FAG 32314-BA参数

尺寸	d	70	mm	-
	D	150	mm	-
	T	54	mm	-
	a	44	mm	-
	B	51	mm	-
	C	42	mm	-
	$C_{a \min}$	7	mm	-
基本额定载荷	$C_{0r}$	395000	N	基本额定静载荷，径向
计算系数	e	0.55		-
	Y	1.1		-
	$Y_0$	0.6		-
疲劳极限载荷	$C_{ur}$	48500	N	疲劳极限载荷，径向
极限转速	$n_G$	4650	r/min	极限转速
参考转速	$n_B$	3550	r/min	参考速度
说明		T5GD070		根据 DIN ISO 355 的 对应型号
尺寸	$C_{b \min}$	12	mm	-
	$D_{a \max}$	138	mm	-
	$D_{a \min}$	117	mm	-
	$D_{b \min}$	143	mm	-
	$d_1$	112	mm	-
	$d_{a \max}$	83	mm	-
	$d_{b \min}$	82	mm	-
	$r_{1, 2 \min}$	3	mm	-
	$r_{3, 4 \min}$	2.5	mm	-
	$r_{a \max}$	3	mm	-
	$r_{b \max}$	2.5	mm	-
重量	m	4520	g	质量

FAG 32314-BA图片

