

NTN KRVT40X/3AS参数

| 型号 | ORDER | KRVT40X/3AS | | 型号 |
|--------|-------|-------------|-------|-----|
| 尺寸 | D | 40 | mm | - |
| | D1 | 18 | mm | - |
| | C | 20 | mm | - |
| | F | 22 | mm | - |
| | B | 21.5 | mm | - |
| | B1 | 58 | mm | - |
| | B2 | 36.5 | mm | - |
| | G | M18x1.5 | | 螺栓 |
| | G1 | 19 | mm | - |
| | C1 | 0.8 | mm | - |
| | E | 32 | mm | - |
| 基本额定载荷 | CR | 19400 | N | 动载荷 |
| | COR | 42000 | N | 静载荷 |
| | CRF | 1980 | kgf | 动载荷 |
| | CORF | 4250 | kgf | 静载荷 |
| | CR2 | 14500 | N | 动载荷 |
| | COR2 | 14500 | N | 静载荷 |
| | CRF2 | 1480 | kgf | 动载荷 |
| | CORF2 | 1480 | kgf | 静载荷 |
| 极限转速 | LSG | 4500 | r/min | 脂润滑 |
| | LSO | 6000 | r/min | 油润滑 |
| 重量 | MASS | 252 | g | 重量 |

NTN KRVT40X/3AS图片

参考资料:<http://www.sozhou.com/p/21bb163a.html>

