




SKF S71904 CD/P4A参数

主要尺寸	d	20	mm	—
	D	37	mm	—
	B	9	mm	—
基本额定载荷	C	6050	N	动载荷
	C_0	3200	N	静载荷
疲劳载荷极限	P_u	137	N	—
可达转速	Grease	43000	r/min	—
	Oil-air	—	r/min	—
重量	重量	37	g	—
型号	型号	S71904 CD/P4A	—	—

SKF S71904 CD/P4A图片



Ball diameter 4,762
Number of balls 15

未安装时的预载荷 [N]
背对背配置，面对面配置
预载荷等级

A	B	C	D
25	50	100	200

Static axial stiffness [N/μm]
(guideline value)

预载荷等级

A	B	C	D
22	29	40	56



Reference grease quantity [cm³]
 G_{ref} —

计算系数
for equivalent bearing load
 f_0 9,8

for preload in mounted bearing sets

f	1,05
f_1	1
f_{2A}	1
f_{2B}	1,04
f_{2C}	1,09
f_{2D}	1,15
f_{HC}	1

参考资料: <http://www.sozhou.com/p/22f7ba1a.html>



Ball diameter 4,762

Number of balls 15

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
25	50	100	200

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
22	29	40	56

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 9,8

for preload in mounted bearing sets

f 1,05

f_1 1

f_{2A} 1

f_{2B} 1,04

f_{2C} 1,09

f_{2D} 1,15

f_{HC} 1