

### FAG 618/750-M参数

|        |              |         |       |             |
|--------|--------------|---------|-------|-------------|
| 极限转速   | $n_G$        | 1110    | r/min | 极限转速        |
| 参考转速   | $n_B$        | 680     | r/min | 参考速度        |
| 疲劳极限载荷 | $C_{ur}$     | 22600   | N     | 疲劳极限载荷, 径向  |
| 尺寸     | $d$          | 750     | mm    | -           |
|        | $D$          | 920     | mm    | -           |
|        | $B$          | 78      | mm    | -           |
|        | $D_1$        | 864.9   | mm    | -           |
|        | $D_{a\ max}$ | 902     | mm    | -           |
|        | $d_1$        | 806.7   | mm    | -           |
|        | $d_{a\ min}$ | 768     | mm    | -           |
|        | $r_{a\ max}$ | 4       | mm    | -           |
|        | $r_{min}$    | 5       | mm    | -           |
| 重量     | $m$          | 114000  | g     | 质量          |
| 基本额定载荷 | $C_r$        | 540000  | N     | 基本额定动载荷, 径向 |
|        | $C_{0r}$     | 1120000 | N     | 基本额定静载荷, 径向 |

### FAG 618/750-M图片





参考资料:<http://www.sozhou.com/p/3620d20d.html>