

### FAG NUP214-E-TVP2参数

尺寸	d	70	mm	-
	D	125	mm	-
	B	24	mm	-
	B <sub>3</sub>	4	mm	-
	D <sub>1</sub>	109.4	mm	-
	D <sub>a max</sub>	116	mm	-
疲劳极限载荷	C <sub>ur</sub>	24300	N	疲劳极限载荷，径向
尺寸	d <sub>c min</sub>	92	mm	-
	F	83.5	mm	-
	r <sub>1 min</sub>	1.5	mm	-
	r <sub>a max</sub>	1.5	mm	-
	r <sub>a1 max</sub>	1.5	mm	-
	r <sub>min</sub>	1.5	mm	-
	s	0	mm	距离中心位置的轴向偏移
重量	m	1200	g	质量
基本额定载荷	C <sub>r</sub>	141000	N	基本额定动载荷，径向
	C <sub>0r</sub>	138000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	6800	r/min	极限转速
参考转速	n <sub>B</sub>	4750	r/min	参考速度
尺寸	d <sub>1</sub>	89.4	mm	-
	d <sub>a max</sub>	82	mm	-
	d <sub>a min</sub>	79	mm	-

### FAG NUP214-E-TVP2图片



参考资料:<http://www.sozhou.com/p/3a9767da.html>

