

### FAG NU2312-E-TVP2参数

尺寸	d	60	mm	-
	D	130	mm	-
	B	46	mm	-
	D <sub>1</sub>	109.6	mm	-
	D <sub>a max</sub>	118	mm	-
	d <sub>a max</sub>	75	mm	-
	d <sub>a min</sub>	72	mm	-
	d <sub>b min</sub>	79	mm	-
	E	115	mm	-
	F	77	mm	-
	r <sub>1 min</sub>	2.1	mm	-
	r <sub>a max</sub>	2.1	mm	-
	r <sub>al max</sub>	2.1	mm	-
	r <sub>min</sub>	2.1	mm	-
	s	3.5	mm	距离中心位置的轴向偏移
重量	m	2780	g	质量
基本额定载荷	C <sub>r</sub>	265000	N	基本额定动载荷，径向
	C <sub>0r</sub>	260000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	6500	r/min	极限转速
参考转速	n <sub>B</sub>	4300	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	50000	N	疲劳极限载荷，径向

### FAG NU2312-E-TVP2图片



参考资料:<http://www.sozhou.com/p/44047b7a.html>

