

### FAG NU320-E-TVP2参数

尺寸	d	100	mm	-
	D	215	mm	-
	B	47	mm	-
	D <sub>1</sub>	182	mm	-
	D <sub>a max</sub>	201	mm	-
	d <sub>a max</sub>	125	mm	-
	d <sub>a min</sub>	114	mm	-
	d <sub>b min</sub>	132	mm	-
	E	191.5	mm	-
	F	127.5	mm	-
	r <sub>1 min</sub>	3	mm	-
	r <sub>a max</sub>	2.5	mm	-
	r <sub>al max</sub>	2.5	mm	-
	r <sub>min</sub>	3	mm	-
	s	1.2	mm	距离中心位置的轴向偏移
重量	m	7670	g	质量
基本额定载荷	C <sub>r</sub>	450000	N	基本额定动载荷，径向
	C <sub>0r</sub>	425000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	3700	r/min	极限转速
参考转速	n <sub>B</sub>	3400	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	53000	N	疲劳极限载荷，径向

### FAG NU320-E-TVP2图片



参考资料:<http://www.sozhou.com/p/49cfa6af.html>

