

## FAG NJ224-E-TVP2参数

尺寸	d	120	mm	-
	D	215	mm	-
	B	40	mm	-
	B <sub>1</sub>	11	mm	-
	B <sub>2</sub>	17	mm	-
	D <sub>1</sub>	187.8	mm	-
	D <sub>a max</sub>	203	mm	-
	d <sub>1</sub>	153.2	mm	-
	d <sub>a max</sub>	141	mm	-
	d <sub>a min</sub>	132	mm	-
	d <sub>c min</sub>	156	mm	-
	F	143.5	mm	-
	r <sub>1 min</sub>	2.1	mm	-
	r <sub>a max</sub>	2.1	mm	-
	r <sub>a1 max</sub>	2.1	mm	-
	r <sub>min</sub>	2.1	mm	-
	s	1.4	mm	距离中心位置的轴向偏移
重量	m	5910	g	质量
基本额定载荷	C <sub>r</sub>	390000	N	基本额定动载荷，径向
	C <sub>0r</sub>	415000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	3750	r/min	极限转速
参考转速	n <sub>B</sub>	3100	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	68000	N	疲劳极限载荷，径向

## FAG NJ224-E-TVP2图片





参考资料:<http://www.sozhou.com/p/4ba891cc.html>