

FAG 30313-A参数

尺寸	d	65	mm	-	
	D	140	mm	-	
	T	36	mm	-	
	a	28	mm	-	
	B	33	mm	-	
	C	28	mm	-	
	$C_{a \text{ min}}$	5	mm	-	
	$C_{b \text{ min}}$	8	mm	-	
	$D_{a \text{ max}}$	128	mm	-	
	$D_{a \text{ min}}$	122	mm	-	
	$D_{b \text{ min}}$	130	mm	-	
	d_1	99.6	mm	-	
	$d_{a \text{ max}}$	83	mm	-	
	$d_{b \text{ min}}$	77	mm	-	
	$r_{1, 2 \text{ min}}$	3	mm	-	
	$r_{3, 4 \text{ min}}$	2.5	mm	-	
	$r_{a \text{ max}}$	3	mm	-	
	$r_{b \text{ max}}$	2.5	mm	-	
	重量	m	2400	g	质量
	基本额定载荷	C_r	196000	N	基本额定动载荷, 径向
C_{0r}		228000	N	基本额定静载荷, 径向	
计算系数	e	0.35		-	
	Y	1.74		-	
	Y_0	0.96		-	
疲劳极限载荷	C_{ur}	27000	N	疲劳极限载荷, 径向	
极限转速	n_G	5300	r/min	极限转速	
参考转速	n_B	3950	r/min	参考速度	

FAG 30313-A图片

