





SKF 7002 CD/HCP4A参数

主要尺寸	d	15	mm	—
	D	32	mm	—
	B	9	mm	—
基本额定载荷	C	5200	N	动载荷
	C_0	2450	N	静载荷
疲劳载荷极限	P_u	104	N	—
可达转速	Grease	67000	r/min	—
	Oil-air	100000	r/min	—
重量	重量	27	g	—
型号	型号	7002 CD/HCP4A	—	—

SKF 7002 CD/HCP4A图片



Ball diameter 4,762

Number of balls 12

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
20	40	80	160

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
19	25	35	49

Reference grease quantity [cm³]

G_{ref} 0,39

计算系数

for equivalent bearing load

f_0 9,3

for preload in mounted bearing sets

f 1,03

f_1 1





f_{2A} 1

f_{2B} 1,02

f_{2C} 1,05

f_{2D} 1,09

f_{HC} 1,02



Ball diameter 4,762
Number of balls 12

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
20	40	80	160

Static axial stiffness [N/ μ m]

(guideline value)

预载荷等级

A	B	C	D
19	25	35	49

Reference grease quantity [cm³]

G_{ref} 0,39

计算系数

for equivalent bearing load

f_0 9,3

for preload in mounted bearing sets

f 1,03

f_1 1

f_{2A} 1

f_{2B} 1,02

f_{2C} 1,05

f_{2D} 1,09

f_{HC} 1,02