


SKF BSA 201 C参数

主要尺寸	d	12	mm	-
	D	32	mm	-
	H	10	mm	-
基本额定载荷	C	11800	N	动载荷
	C_0	21200	N	静载荷
疲劳载荷极限	P_u	800	N	-
可达转速	Grease lubrication	14000	r/min	-
	Oil-air lubrication	17000	r/min	-
重量	重量	43	g	-
型号	型号	BSA 201 C	-	-

SKF BSA 201 C图片



Preload¹⁾ [N]

Frictional moment¹⁾ [Nm]
(guideline value)

Static axial stiffness¹⁾ [N/μm]
(guideline value)

¹⁾ Values apply to unmounted bearing set with two bearings arranged back-to-back or face-to-face




预载荷等级

	A	B
Preload ¹⁾ [N]	650	1300
Frictional moment ¹⁾ [Nm] (guideline value)	0,016	0,028
Static axial stiffness ¹⁾ [N/μm] (guideline value)	400	510

Max. axial load carrying capacity
(guideline value)

Reference grease quantity [cm³]
 G_{ref} 0,4

参考资料: <http://www.sozhou.com/p/60fa08e3.html>



预载荷等级

	A	B
Preload¹⁾ [N]	650	1300
Frictional moment¹⁾ [Nm] (guideline value)	0,016	0,028
Static axial stiffness¹⁾ [N/μm] (guideline value)	400	510

Max. axial load carrying capacity

(guideline value)
6,25

Reference grease quantity [cm³]

G_{ref} 0,4

Preload¹⁾ [N]

Frictional moment¹⁾ [Nm]

(guideline value)

Static axial stiffness¹⁾ [N/μm]

(guideline value)

¹⁾ Values apply to unmounted bearing set with two bearings arranged back-to-back or face-to-face