




SKF S71906 CB/P4A参数

主要尺寸	d	30	mm	—
	D	47	mm	—
	B	9	mm	—
基本额定载荷	C	4880	N	动载荷
	C_0	3150	N	静载荷
疲劳载荷极限	P_u	134	N	—
可达转速	Grease	40000	r/min	—
	Oil-air	—	r/min	—
重量	重量	50	g	—
型号	型号	S71906 CB/P4A	—	—

SKF S71906 CB/P4A图片



Ball diameter 3,969

Number of balls 22

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
16	32	96	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
20	27	43	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 9,5

for preload in mounted bearing sets

f 1,07

f_1 1

f_{2A} 1




f_{2B} 1,02

f_{2C} 1,07

f_{2D} -

f_{HC} 1

参考资料: <http://www.sozhou.com/p/7475646f.html>



Ball diameter 3,969

Number of balls 22

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
16	32	96	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
20	27	43	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 9,5

for preload in mounted bearing sets

f 1,07

f_1 1

f_{2A} 1

f_{2B} 1,02

f_{2C} 1,07

f_{2D} -

f_{HC} 1