

## FAG 32224-A参数

尺寸	d	120	mm	-
	D	215	mm	-
	T	61.5	mm	-
	a	51	mm	-
	B	58	mm	-
	C	50	mm	-
	C <sub>a min</sub>	7	mm	-
	C <sub>b min</sub>	11.5	mm	-
	D <sub>a max</sub>	203	mm	-
	D <sub>a min</sub>	181	mm	-
	D <sub>b min</sub>	204	mm	-
	d <sub>1</sub>	165.2	mm	-
	d <sub>a max</sub>	136	mm	-
	d <sub>b min</sub>	132	mm	-
	r <sub>1, 2 min</sub>	3	mm	-
	极限转速	n <sub>G</sub>	3150	r/min
参考转速	n <sub>B</sub>	2120	r/min	参考速度
说明		T4FD120		根据 DIN ISO 355 的 对应型号
尺寸	r <sub>3, 4 min</sub>	2.5	mm	-
	r <sub>a max</sub>	3	mm	-
	r <sub>b max</sub>	2.5	mm	-
重量	m	9300	g	质量
基本额定载荷	C <sub>r</sub>	485000	N	基本额定动载荷，径向
	C <sub>0r</sub>	730000	N	基本额定静载荷，径向
计算系数	e	0.44		-
	Y	1.38		-
	Y <sub>0</sub>	0.76		-

FAG 32224-A图片

