

FAG 31310-A参数

尺寸	$r_{3, 4 \text{ min}}$	2	mm	-
	$r_{a \text{ max}}$	2.5	mm	-
	$r_{b \text{ max}}$	2	mm	-
重量	m	1230	g	质量
基本额定载荷	C_r	111000	N	基本额定动载荷, 径向
	C_{0r}	125000	N	基本额定静载荷, 径向
计算系数	e	0.83		-
	Y	0.73		-
	Y_0	0.4		-
疲劳极限载荷	C_{ur}	14700	N	疲劳极限载荷, 径向
极限转速	n_G	6500	r/min	极限转速
参考转速	n_B	4300	r/min	参考速度
说明		T7FB050		根据 DIN ISO 355 的 对应型号
尺寸	d	50	mm	-
	D	110	mm	-
	T	29.25	mm	-
	a	35	mm	-
	B	27	mm	-
	C	19	mm	-
	$C_{a \text{ min}}$	4	mm	-
	$C_{b \text{ min}}$	10	mm	-
	$D_{a \text{ max}}$	100	mm	-
	$D_{a \text{ min}}$	87	mm	-
	$D_{b \text{ min}}$	104	mm	-
	d_1	81.4	mm	-
	$d_{a \text{ max}}$	62	mm	-
	$d_{b \text{ min}}$	60	mm	-

FAG 31310-A图片

