

FAG 30208-A参数

尺寸	$C_{a \min}$	3	mm	-	
	$C_{b \min}$	3.5	mm	-	
	$D_{a \max}$	73	mm	-	
	$D_{a \min}$	69	mm	-	
	$D_{b \min}$	74	mm	-	
	d_1	58.4	mm	-	
	$d_{a \max}$	49	mm	-	
	d	40	mm	-	
	D	80	mm	-	
	T	19.75	mm	-	
	a	17	mm	-	
	B	18	mm	-	
	C	16	mm	-	
	$d_{b \min}$	47	mm	-	
	$r_{1, 2 \min}$	1.5	mm	-	
	$r_{3, 4 \min}$	1.5	mm	-	
	$r_{a \max}$	1.5	mm	-	
	$r_{b \max}$	1.5	mm	-	
	重量	m	435	g	质量
	基本额定载荷	C_r	61000	N	基本额定动载荷，径向
C_{0r}		67000	N	基本额定静载荷，径向	
计算系数	e	0.37		-	
	Y	1.6		-	
	Y_0	0.88		-	
疲劳极限载荷	C_{ur}	7600	N	疲劳极限载荷，径向	
极限转速	n_G	9600	r/min	极限转速	
参考转速	n_B	5900	r/min	参考速度	

FAG 30208-A图片

