

## FAG 30203-A参数

疲劳极限载荷	$C_{ur}$	1890	N	疲劳极限载荷，径向	
极限转速	$n_G$	20100	r/min	极限转速	
参考转速	$n_B$	12100	r/min	参考速度	
说明		T2DB017		根据 DIN ISO 355 的 对应型号	
尺寸	d	17	mm	-	
	D	40	mm	-	
	T	13.25	mm	-	
	a	10	mm	-	
	B	12	mm	-	
	C	11	mm	-	
	$C_{a \min}$	2	mm	-	
	$C_{b \min}$	2	mm	-	
	$D_{a \max}$	34	mm	-	
	$D_{a \min}$	34	mm	-	
	$D_{b \min}$	37	mm	-	
	$d_1$	29.1	mm	-	
	$d_{a \max}$	23	mm	-	
	$d_{b \min}$	23	mm	-	
	$r_{1, 2 \min}$	1	mm	-	
	$r_{3, 4 \min}$	1	mm	-	
	$r_{a \max}$	1	mm	-	
	$r_{b \max}$	1	mm	-	
	重量	m	56	g	质量
	基本额定载荷	$C_r$	19200	N	基本额定动载荷，径向
$C_{0r}$		18700	N	基本额定静载荷，径向	
计算系数	e	0.35		-	
	Y	1.74		-	

FAG 30203-A图片

