




SKF S7011 CE/P4A参数

主要尺寸	d	55	mm	—
	D	90	mm	—
	B	18	mm	—
基本额定载荷	C	16800	N	动载荷
	C_0	12200	N	静载荷
疲劳载荷极限	P_u	520	N	—
可达转速	Grease	22000	r/min	—
	Oil-air	—	r/min	—
重量	重量	400	g	—
型号	型号	S7011 CE/P4A	—	—

SKF S7011 CE/P4A图片



Ball diameter 7,938

Number of balls 24

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
90	270	540	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
46	72	98	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 8,4

for preload in mounted bearing sets

f 1,07

f_1 1

f_{2A} 1




f_{2B} 1,03

f_{2C} 1,05

f_{2D} -

f_{HC} 1

参考资料: <http://www.sozhou.com/p/8f287aea.html>



Ball diameter 7,938

Number of balls 24

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
90	270	540	-

Static axial stiffness [N/ μ m]

(guideline value)

预载荷等级

A	B	C	D
46	72	98	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 8,4

for preload in mounted bearing sets

f 1,07

f_1 1

f_{2A} 1

f_{2B} 1,03

f_{2C} 1,05

f_{2D} -

f_{HC} 1