

TIMKEN 34306/34478参数

轴承类型	Bearing Type	TRB		-
子类	Bearing Subtype	TS		-
尺寸	Cone (Inner)	34306		内圈
	Cup (Outer)	34478		外圈
额定载荷	d	77.7875	mm	内径
	D	121.442	mm	外径
	T	24.6126	mm	宽度
	C1	120992	N	一百万转动态径向载荷
	C90	31404.4	N	九千万转动态径向载荷
	Ca90	24242.8	N	九千万转单列轴承动态轴向载荷
	C0	136116	N	静态额定载荷
尺寸	$K = 0.39 / \tan(\text{contact angle})$	1.30		系数
	$e = 1.5 * \tan(\text{contact angle})$	0.45		系数
	$Y = 0.4 / \tan(\text{contact angle})$	1.33		系数
几何结构系数	Cg	0.1093		几何系数
尺寸	B	23.0124	mm	内圈宽度
	R	3.556	mm	最大轴肩倒角半径
	db	90.932	mm	轴肩直径
	da	84.074	mm	轴肩直径
	Aa	2.54	mm	保持架（负值表示保持架超出内圈大端面）
	Ab	2.032	mm	保持架（负值表示保持架没超出内圈小端面）
	C	17.4625	mm	外圈宽度
	r	2.032	mm	最大轴承座挡肩圆角半径
	Db	109.982	mm	轴承座挡肩直径
	Da	116.078	mm	轴承座挡肩直径
	a	1.524	mm	有效中心位置
重量	Assembly Weight	911.72	g	-

TIMKEN 34306/34478图片







参考资料:<http://www.sozhou.com/p/8f6ca50c.html>

