

FAG 22260-K-MB + H3160参数

尺寸	l	208	mm	-
	n_s	23.5	mm	-
	$r_{a \max}$	4	mm	-
	r_{\min}	5	mm	-
说明		H3160		质量, 紧定套
重量	m	136000	g	质量
	m_1	30600	g	质量, 紧定套
基本额定载荷	C_r	2750000	N	基本额定动载荷, 径向
计算系数	e	0.27		-
	Y_1	2.47		-
	Y_2	3.67		-
基本额定载荷	C_{0r}	4400000	N	基本额定静载荷, 径向
计算系数	Y_0	2.41		-
极限转速	n_G	1490	r/min	极限转速
尺寸	d_{1H}	280	mm	-
	D	540	mm	-
	B	140	mm	-
	$B_{a \min}$	32	mm	-
	c	40	mm	-
	c_1	53	mm	-
	D_1	468.8	mm	-
	$D_{a \max}$	520	mm	-
	D_m	380	mm	-
	d	300	mm	-
	$d_{a \max}$	352	mm	-
	$d_{b \min}$	318	mm	-
	d_s	12.5	mm	-

参考转速	n_B	900	r/min	参考速度
疲劳极限载荷	C_{ur}	300000	N	疲劳极限载荷，径向

FAG 22260-K-MB + H3160图片

