

FAG NU318-E-TVP2参数

| | | | | |
|--------|---------------------|--------|-------|-------------|
| 尺寸 | d | 90 | mm | - |
| | D | 190 | mm | - |
| | B | 43 | mm | - |
| | D ₁ | 161.6 | mm | - |
| | D _{a max} | 176 | mm | - |
| | d _{a max} | 111 | mm | - |
| | d _{a min} | 104 | mm | - |
| | d _{b min} | 117 | mm | - |
| | E | 169.5 | mm | - |
| | F | 113.5 | mm | - |
| | r _{1 min} | 3 | mm | - |
| | r _{a max} | 2.5 | mm | - |
| | r _{al max} | 2.5 | mm | - |
| | r _{min} | 3 | mm | - |
| | s | 1.5 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 5390 | g | 质量 |
| 基本额定载荷 | C _r | 370000 | N | 基本额定动载荷，径向 |
| | C _{0r} | 350000 | N | 基本额定静载荷，径向 |
| 极限转速 | n _G | 4250 | r/min | 极限转速 |
| 参考转速 | n _B | 3750 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 44500 | N | 疲劳极限载荷，径向 |

FAG NU318-E-TVP2图片



参考资料:<http://www.sozhou.com/p/92f032a7.html>

