





SKF 71808 CD/P4参数

主要尺寸	d	40	mm	—
	D	52	mm	—
	B	7	mm	—
基本额定载荷	C	4880	N	动载荷
	C_0	4900	N	静载荷
疲劳载荷极限	P_u	208	N	—
可达转速	Grease	26000	r/min	—
	Oil-air	38000	r/min	—
重量	重量	31	g	—
型号	型号	71808 CD/P4	—	—

SKF 71808 CD/P4图片



Ball diameter 3,175

Number of balls 29

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
19	58	115	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
36	61	90	-

Reference grease quantity [cm³]

G_{ref} 0,31

计算系数

for equivalent bearing load

f_0 17,2

for preload in mounted bearing sets

f 1,23

f_1 1





f_{2A} 1

f_{2B} 1,09

f_{2C} 1,16

f_{2D} -

f_{HC} 1



Ball diameter 3,175
Number of balls 29

未安装时的预载荷 [N]
 背对背配置，面对面配置
 预载荷等级

A	B	C	D
19	58	115	-

Static axial stiffness [N/ μ m]
 (guideline value)

预载荷等级	A	B	C	D
	36	61	90	-

Reference grease quantity [cm³]
 G_{ref} 0,31

计算系数
for equivalent bearing load
 f_0 17,2

for preload in mounted bearing sets

f	1,23
f_1	1
f_{2A}	1
f_{2B}	1,09
f_{2C}	1,16
f_{2D}	-
f_{HC}	1