





SKF 71806 CD/P4参数

主要尺寸	d	30	mm	—
	D	42	mm	—
	B	7	mm	—
基本额定载荷	C	4420	N	动载荷
	C_0	3750	N	静载荷
疲劳载荷极限	P_u	160	N	—
可达转速	Grease	32000	r/min	—
	Oil-air	50000	r/min	—
重量	重量	26	g	—
型号	型号	71806 CD/P4	—	—

SKF 71806 CD/P4图片



Ball diameter 3,175

Number of balls 23

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
17	52	105	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
29	49	72	-

Reference grease quantity [cm³]

G_{ref} 0,24

计算系数

for equivalent bearing load

f_0 16,8

for preload in mounted bearing sets

f 1,14

f_1 1





f_{2A} 1

f_{2B} 1,09

f_{2C} 1,16

f_{2D} -

f_{HC} 1



Ball diameter 3,175

Number of balls 23

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
17	52	105	-

Static axial stiffness [N/ μ m]

(guideline value)

预载荷等级

A	B	C	D
29	49	72	-

Reference grease quantity [cm³]

G_{ref} 0,24

计算系数

for equivalent bearing load

f_0 16,8

for preload in mounted bearing sets

f 1,14

f_1 1

f_{2A} 1

f_{2B} 1,09

f_{2C} 1,16

f_{2D} -

f_{HC} 1