

FAG 30324-A参数

尺寸	d	120	mm	-	
	D	260	mm	-	
	T	59.5	mm	-	
	a	48	mm	-	
	B	55	mm	-	
	C	46	mm	-	
	C <sub>a min</sub>	10	mm	-	
	C <sub>b min</sub>	13.5	mm	-	
	D <sub>a max</sub>	246	mm	-	
	D <sub>a min</sub>	221	mm	-	
	D <sub>b min</sub>	237	mm	-	
	d <sub>1</sub>	183.5	mm	-	
	d <sub>a max</sub>	152	mm	-	
	d <sub>b min</sub>	134	mm	-	
	r <sub>1, 2 min</sub>	4	mm	-	
	r <sub>3, 4 min</sub>	3	mm	-	
	r <sub>a max</sub>	4	mm	-	
	r <sub>b max</sub>	3	mm	-	
	重量	m	14300	g	质量
	基本额定载荷	C <sub>r</sub>	560000	N	基本额定动载荷, 径向
C <sub>0r</sub>		700000	N	基本额定静载荷, 径向	
计算系数	e	0.35		-	
	Y	1.74		-	
	Y <sub>0</sub>	0.96		-	
疲劳极限载荷	C <sub>ur</sub>	83000	N	疲劳极限载荷, 径向	
极限转速	n <sub>G</sub>	2800	r/min	极限转速	
参考转速	n <sub>B</sub>	2160	r/min	参考速度	

FAG 30324-A图片

