

FAG NU319-E-TVP2参数

| | | | | |
|--------|---------------------|--------|-------|-------------|
| 尺寸 | d | 95 | mm | - |
| | D | 200 | mm | - |
| | B | 45 | mm | - |
| | D ₁ | 169.6 | mm | - |
| | D _{a max} | 186 | mm | - |
| | d _{a max} | 119 | mm | - |
| | d _{a min} | 109 | mm | - |
| | d _{b min} | 124 | mm | - |
| | E | 177.5 | mm | - |
| | F | 121.5 | mm | - |
| | r _{1 min} | 3 | mm | - |
| | r _{a max} | 2.5 | mm | - |
| | r _{al max} | 2.5 | mm | - |
| | r _{min} | 3 | mm | - |
| | s | 1.4 | mm | 距离中心位置的轴向偏移 |
| 重量 | m | 6320 | g | 质量 |
| 基本额定载荷 | C _r | 390000 | N | 基本额定动载荷，径向 |
| | C _{0r} | 380000 | N | 基本额定静载荷，径向 |
| 极限转速 | n _G | 4050 | r/min | 极限转速 |
| 参考转速 | n _B | 3600 | r/min | 参考速度 |
| 疲劳极限载荷 | C _{ur} | 48000 | N | 疲劳极限载荷，径向 |

FAG NU319-E-TVP2图片



参考资料:<http://www.sozhou.com/p/a3af72da.html>

