

### NACHI 29412EX参数

|        |           |         |       |      |
|--------|-----------|---------|-------|------|
| 外形尺寸   | d         | 60      | mm    | 内径   |
|        | D         | 130     | mm    | 外径   |
|        | T         | 42      | mm    | 宽度   |
|        | r         | 1.5~3.5 | mm    | 倒角   |
| 参考尺寸   | d1        | 113     | mm    | -    |
|        | D1        | 87      | mm    | -    |
|        | B         | 27      | mm    | -    |
|        | B1        | 37.1    | mm    | -    |
|        | C         | 20      | mm    | -    |
|        | A         | 38      | mm    | -    |
| 安装尺寸   | da (min)  | 91      | mm    | (最小) |
|        | Da (max)  | 108     | mm    | (最大) |
|        | ra (max)  | 1.5     | mm    | (最大) |
|        | db1 (max) | 66      | mm    | (最大) |
|        | db2 (max) | 66      | mm    | (最大) |
| 重量     | Mass      | 2500    | g     | 重量   |
| 基本额定载荷 | Ca        | 350000  | N     | 动载荷  |
|        | Coa       | 915000  | N     | 静载荷  |
| 极限速度   | Grease    | 1800    | r/min | 脂润滑  |
|        | Oil       | 2800    | r/min | 油润滑  |

### NACHI 29412EX图片

参考资料:<http://www.sozhou.com/p/a9eaf751.html>

