




SKF S7017 CD/HCP4A参数

主要尺寸	d	85	mm	—
	D	130	mm	—
	B	22	mm	—
基本额定载荷	C	67600	N	动载荷
	C_0	65500	N	静载荷
疲劳载荷极限	P_u	2650	N	—
可达转速	Grease	12000	r/min	—
	Oil-air	—	r/min	—
重量	重量	760	g	—
型号	型号	S7017 CD/HCP4A	—	—

SKF S7017 CD/HCP4A图片



Ball diameter 14,288

Number of balls 21

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
250	500	1000	2000

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
107	146	205	298

Reference grease quantity [cm³]

G_{ref} —

计算系数

for equivalent bearing load

f_0 15,7

for preload in mounted bearing sets

f 1,15

f_1 1

f_{2A} 1



f_{2B} 1,02

f_{2C} 1,05

f_{2D} 1,09

f_{HC} 1,02

参考资料: <http://www.sozhou.com/p/b47b1472.html>



Ball diameter 14,288

Number of balls 21

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
250	500	1000	2000

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
107	146	205	298

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 15,7

for preload in mounted bearing sets

f 1,15

f_1 1

f_{2A} 1

f_{2B} 1,02

f_{2C} 1,05

f_{2D} 1,09

f_{HC} 1,02