

FAG B7207-E-2RSD-T-P4S参数

|        |               |       |       |             |
|--------|---------------|-------|-------|-------------|
| 尺寸     | d             | 35    | mm    | -           |
|        | D             | 72    | mm    | -           |
|        | B             | 17    | mm    | -           |
|        | a             | 21    | mm    | -           |
|        | $D_a$ H12     | 63    | mm    | -           |
|        | $d_a$ h12     | 44    | mm    | -           |
|        | $r_{1\ min}$  | 1.1   | mm    | -           |
|        | $r_{a\ max}$  | 1     | mm    | -           |
|        | $r_{al\ max}$ | 1     | mm    | -           |
|        | $r_{\min}$    | 1.1   | mm    | -           |
|        | 重量            | m     | 308   | g           |
| 基本额定载荷 | $C_r$         | 30000 | N     | 基本额定动载荷, 径向 |
|        | $C_{0r}$      | 17100 | N     | 基本额定静载荷, 径向 |
| 极限转速   | $n_{G\ Fett}$ | 19000 | r/min | 脂润滑时的极限转速   |
| 疲劳极限载荷 | $C_{ur}$      | 1790  | N     | 疲劳极限载荷, 径向  |

FAG B7207-E-2RSD-T-P4S图片



