

## TIMKEN 3382/3325参数

轴承类型	Bearing Type	TRB		-	
子类	Bearing Subtype	TS		-	
尺寸	Cone (Inner)	3382		内圈	
	Cup (Outer)	3325		外圈	
尺寸	d	39.6875	mm	内径	
	D	79.9744	mm	外径	
	T	29.3624	mm	宽度	
	额定载荷	C1	114764	N	一百万转动态径向载荷
		C90	29803.1	N	九千万转动态径向载荷
		Ca90	13922.9	N	九千万转单列轴承动态轴向载荷
	C0	129443	N	静态额定载荷	
	$K = 0.39 / \tan$ (contact angle)	2.14		系数	
	$e = 1.5 * \tan$ (contact angle)	0.27		系数	
尺寸	$Y = 0.4 / \tan$ (contact angle)	2.20		系数	
几何结构系数	Cg	0.0744		几何系数	
尺寸	B	30.3911	mm	内圈宽度	
	R	3.556	mm	最大轴肩倒角半径	
	db	52.07	mm	轴肩直径	
	da	45.466	mm	轴肩直径	
	Aa	1.778	mm	保持架（负值表示保持架超出内圈大端面）	
	Ab	1.016	mm	保持架（负值表示保持架没超出内圈小端面）	
	C	23.8125	mm	外圈宽度	
	r	3.302	mm	最大轴承座挡肩圆角半径	
	Db	70.104	mm	轴承座挡肩直径	
	Da	74.676	mm	轴承座挡肩直径	
	a	-10.922	mm	有效中心位置	
重量	Assembly Weight	644.10	g	-	

TIMKEN 3382/3325图片







参考资料:<http://www.sozhou.com/p/bafa89f8.html>

