




SKF S7020 CE/HCP4A参数

主要尺寸	d	100	mm	—
	D	150	mm	—
	B	24	mm	—
基本额定载荷	C	44900	N	动载荷
	C_0	40000	N	静载荷
疲劳载荷极限	P_u	1500	N	—
可达转速	Grease	14500	r/min	—
	Oil-air	—	r/min	—
重量	重量	1200	g	—
型号	型号	S7020 CE/HCP4A	—	—

SKF S7020 CE/HCP4A图片



Ball diameter 12,7

Number of balls 27

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
240	720	1440	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
97	154	212	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 9,5

for preload in mounted bearing sets

f 1,12

f_1 1

f_{2A} 1




f_{2B} 1,03

f_{2C} 1,05

f_{2D} -

f_{HC} 1,01

参考资料: <http://www.sozhou.com/p/ceb204f4.html>



Ball diameter 12,7

Number of balls 27

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
240	720	1440	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
97	154	212	-

Reference grease quantity [cm³]

G_{ref} -

计算系数

for equivalent bearing load

f_0 9,5

for preload in mounted bearing sets

f 1,12

f_1 1

f_{2A} 1

f_{2B} 1,03

f_{2C} 1,05

f_{2D} -

f_{HC} 1,01