


SKF 707 CE/P4AH参数

主要尺寸	d	7	mm	-
	D	19	mm	-
	B	6	mm	-
基本额定载荷	C	1950	N	动载荷
	C_0	640	N	静载荷
疲劳载荷极限	P_u	27	N	-
可达转速	Grease	127000	r/min	-
	Oil-air	190000	r/min	-
重量	重量	7	g	-
型号	型号	707 CE/P4AH	-	-

SKF 707 CE/P4AH图片



Ball diameter 3,572

Number of balls 8

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
10	30	60	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
8	13	18	-

Reference grease quantity [cm³]

G_{ref} 0,11

计算系数

for equivalent bearing load

f_0 6,5

for preload in mounted bearing sets

f 1,02

f_1 1

f_{2A} 1





f_{2B} 1,03

f_{2C} 1,05

f_{2D} -

f_{HC} 1

参考资料: <http://www.sozhou.com/p/db44ab03.html>



Ball diameter 3,572

Number of balls 8

未安装时的预载荷 [N]

背对背配置，面对面配置

预载荷等级

A	B	C	D
10	30	60	-

Static axial stiffness [N/μm]

(guideline value)

预载荷等级

A	B	C	D
8	13	18	-

Reference grease quantity [cm³]

G_{ref} 0,11

计算系数

for equivalent bearing load

f₀ 6,5

for preload in mounted bearing sets

f 1,02

f₁ 1

f_{2A} 1

f_{2B} 1,03

f_{2C} 1,05

f_{2D} -

f_{HC} 1