

### FAG NU2308-E-TVP2参数

尺寸	d	40	mm	-
	D	90	mm	-
	B	33	mm	-
	D <sub>1</sub>	75.9	mm	-
	D <sub>a max</sub>	81	mm	-
	d <sub>a max</sub>	51	mm	-
	d <sub>a min</sub>	49	mm	-
	d <sub>b min</sub>	55	mm	-
	E	80	mm	-
	F	52	mm	-
	r <sub>1 min</sub>	1.5	mm	-
	r <sub>a max</sub>	1.5	mm	-
	r <sub>al max</sub>	1.5	mm	-
	r <sub>min</sub>	1.5	mm	-
	s	2.7	mm	距离中心位置的轴向偏移
重量	m	958	g	质量
基本额定载荷	C <sub>r</sub>	132000	N	基本额定动载荷，径向
	C <sub>0r</sub>	119000	N	基本额定静载荷，径向
极限转速	n <sub>G</sub>	9500	r/min	极限转速
参考转速	n <sub>B</sub>	6000	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	21600	N	疲劳极限载荷，径向

### FAG NU2308-E-TVP2图片



参考资料:<http://www.sozhou.com/p/dbf7d0fc.html>

