

FAG 23064-K-MB + H3064参数

尺寸	d_{1H}	300	mm	-
	D	480	mm	-
	B	121	mm	-
	$B_{a \min}$	13	mm	-
	c	42	mm	-
	c_1	56	mm	-
	D_1	432.6	mm	-
	$D_{a \max}$	465.4	mm	-
	D_m	380	mm	-
	d	320	mm	-
	$d_{a \max}$	357	mm	-
	$d_{b \min}$	334	mm	-
	d_s	9.5	mm	-
	l	171	mm	-
	n_s	17.7	mm	-
	$r_{a \max}$	3	mm	-
	r_{\min}	4	mm	-
说明		H3064		质量, 紧定套
重量	m	77100	g	质量
	m_1	25400	g	质量, 紧定套
基本额定载荷	C_r	2040000	N	基本额定动载荷, 径向
计算系数	e	0.25		-
	Y_1	2.74		-
	Y_2	4.08		-
基本额定载荷	C_{0r}	4000000	N	基本额定静载荷, 径向
计算系数	Y_0	2.68		-
极限转速	n_G	1460	r/min	极限转速

参考转速	n_B	910	r/min	参考速度
疲劳极限载荷	C_{ur}	243000	N	疲劳极限载荷，径向

FAG 23064-K-MB + H3064图片

