

FAG 32024-X参数

尺寸	d	120	mm	-	
	D	180	mm	-	
	T	38	mm	-	
	a	40	mm	-	
	B	38	mm	-	
	C	29	mm	-	
	$C_a \text{ min}$	7	mm	-	
	$C_b \text{ min}$	9	mm	-	
	$D_a \text{ max}$	170	mm	-	
	$D_a \text{ min}$	161	mm	-	
	$D_b \text{ min}$	173	mm	-	
	d_1	151	mm	-	
	$d_a \text{ max}$	131	mm	-	
	$d_b \text{ min}$	130	mm	-	
	$r_{1, 2} \text{ min}$	2.5	mm	-	
	$r_{3, 4} \text{ min}$	2	mm	-	
	$r_a \text{ max}$	2.5	mm	-	
	$r_b \text{ max}$	2	mm	-	
	重量	m	3290	g	质量
	基本额定载荷	C_r	250000	N	基本额定动载荷, 径向
C_{0r}		420000	N	基本额定静载荷, 径向	
计算系数	e	0.46		-	
	Y	1.31		-	
	Y_0	0.72		-	
疲劳极限载荷	C_{ur}	47500	N	疲劳极限载荷, 径向	
极限转速	n_G	3700	r/min	极限转速	
参考转速	n_B	2460	r/min	参考速度	

FAG 32024-X图片

