

### FAG 22216-E1-K参数

尺寸	d	80	mm	-
	D	140	mm	-
	B	33	mm	-
	D <sub>1</sub>	126.8	mm	-
	D <sub>a max</sub>	129	mm	-
	d <sub>2</sub>	94.9	mm	-
	d <sub>a min</sub>	91	mm	-
	d <sub>s</sub>	3.2	mm	-
	n <sub>s</sub>	6.5	mm	-
	r <sub>a max</sub>	2	mm	-
	r <sub>min</sub>	2	mm	-
	重量	m	2080	g
基本额定载荷	C <sub>r</sub>	250000	N	基本额定动载荷，径向
尺寸	e	0.22		-
计算系数	Y <sub>1</sub>	3.14		-
	Y <sub>2</sub>	4.67		-
基本额定载荷	C <sub>0r</sub>	270000	N	基本额定静载荷，径向
计算系数	Y <sub>0</sub>	3.07		-
极限转速	n <sub>G</sub>	6200	r/min	极限转速
参考转速	n <sub>B</sub>	3700	r/min	参考速度
疲劳极限载荷	C <sub>ur</sub>	33500	N	疲劳极限载荷，径向

### FAG 22216-E1-K图片



参考资料:<http://www.sozhou.com/p/ee342fce.html>